


Professional Choice for Your Marking Job

UDAY  [®]
UDYOG
ELECTRONICS (P) LTD

P
PUTY

TUBE MARKING PRINTER



SPECIFICATIONS

Printing Method:	Thermal Transfer Printing	Weight:	2.8Kg (N.W), 5.95Kg (G.W)
Printing Resolution:	300dpi	Dimension:	298mm(L) x 260mm(W) x 100mm(H)
Power-off Memory:	Yes	Silicone Keyboard:	QWERTY,66 Keys
Consumables:	Label Tape/ PVC Tube/ Heat Shrink Tube	Power Adapter:	100-240V~ 50/ 60Hz 12V —3.0A
Label Size:	6-12mm	Cutting Mode:	Auto Half-cutting/ Manual Full-cutting
Tube Size:	0.5 ² -8 ²	Display:	Cold Light Screen,12 characters/ Max 2 Lines
Heat Shrink Tube Size:	Φ1.0-Φ8.0	Feature:	Unique selection printing for any paragraph printing
Printing Speed:	30mm/s Max 40pcs/ Min Printing 20mm labels/tubes, consecutive print mode, half-cutting	Operating Environment:	5°C~45°C Humidity 20%~85%(No Condensation)
		Built-in Memory:	Memorize max 50 files, 99 paragraphs storing space for each file

CONSUMABLES



Label Tape

Size Color	6mmx8m	9mmx8m	12mmx8m
White	PT-1006W	PT-1009W	PT-1012W
Yellow	PT-1006Y	PT-1009Y	PT-1012Y
Silver	PT-1006S	PT-1009S	PT-1012S



Ribbon Cassette

Size Color	12mmx80m
White	PT-10WE
Black	PT-10BK
Red	PT-10RD

PT-3100P

portable & PC Connecting Label Printer

PC Connecting Explores A Bigger Label World



PC Connection



Width



Resolution



Speed



Auto Cutter



Space adjustment



IMPORTED & MARKETING BY :

UDAY UDYOG ELECTRONICS PVT. LTD.

6-1-339/11, ROAD NO 1, PADMA RAO NAGAR,
SECUNDERABAD - 500 025

Phone : +91-40-27506475/76

Mobile : +91-89499 11630

EMAIL : support@udayudyog.com

frontoffice@udayudyog.com

REPRESENTED BY: